

Rotary Hammer LXT®

DHR242Z

18V • SDS-Plus • 24 mm • 2.0 J

Professional brushless, three-mode rotary hammer

An efficient rotary hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min⁻¹. Impact energy of 2.0 J and max. drilling capacity of 24 mm in concrete. Tool only, battery and charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 950 min ⁻¹
Impacts per Minute (IPM)	0 - 4700 min ⁻¹
Max. Drilling Diameter in Wood	27 mm
Max. Drilling Diameter in Concrete	24 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	6 - 12 mm
Impact Energy	2,0 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Electronic brake	✓
Sound Power Level (L _{WA})	101 dB(A)

User benefits

- Brushless maintenance-free and long-life motor
- Body model - delivered without battery and charger.
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381654326

Link to product - www.makita.com



Related products

Standard AC

324219-0
Depth Gauge

Optional AC

196165-5
HEPA filter



199557-7
Replacement Hepa filter



199977-5
Hepa Filter



324219-0
Depth Gauge



424474-5
Sealing Cap



821552-6
Makpac case (4)



835A31-4
MakPac Type 4 Inlay



D-16368
Chisel set SDS-PLUS, 5 pcs



Other

User manual

Parts drawing