

Reciprocating Saw LXT®

DJR185Z

18V • 0 – 3 300 min⁻¹ • 13 mm

Compact reciprocating saw for light use, also accepts jigsaw bits

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between 0 – 3 300 min⁻¹ from a switch. LED light. Tool only, battery and charger not included.



■ Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Strokes per Minute (SPM)	0 - 3000 min ⁻¹
Length of Stroke	13 mm
Max. Cutting Capacity in Wood (90°)	50 mm
Max. Cutting Capacity in Steel Pipe	50 mm
Sound Pressure Level (L _{pA})	76 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	8,0 m/s ²
Vibration Level (3 axes), Cutting Chipboard	8,0 m/s ²
Vibration Level (3 axes), Cutting Wood	7,0 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery	1,5 - 1,8 kg
Product Dimensions (L x W x H):	398 x 81 x 220 mm

■ User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low
- Body model - delivered without battery and charger.

■ **EAN 0088381652353**

Link to product - www.makita.com



Related products

■ Standard AC

783201-2

Hex Wrench 3Mm



■ Optional AC

821550-0

Makpac case (2)



837897-2

MakPac Type 2 Inner Tray



■ Other

[User manual](#)

[Parts drawing](#)