

Multi tool LXT®

DTM52Z

18V • 10 000 - 20 000 min⁻¹

Multi-tool for cutting, polishing, grout removal and other applications.

A handy 18V LXT® multi-function tool for a variety of cutting and polishing applications in construction and renovation projects, compatible with STARLOCK MAX. Equipped with a tool-less accessory clamp and the oscillating rate can be adjusted between 10 000 and 20 000 min⁻¹. Tool only, battery and a charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Orbits per Minute	10000 - 20000 min ⁻¹
Oscillation Angle	2 x 1,8 °
Pad size (triangle)	93 x 93 x 93 mm
Sound Pressure Level (L _{pA})	69 - 76 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Level (3 axes), Cutting Chipboard	≤ 2,5 m/s ²
Vibration Level (3 axes), Sanding	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery	1,7 - 2,0 kg
Product Dimensions (L x W x H):	332 x 95 x 125 mm
Brushless Motor	✓

User benefits

- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- The rubber coating on the handle ensures a firm working grip
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381741316

Link to product - www.makita.com



Related products

■ Optional AC

191R02-6
Dust Attachment set



835W93-4
Inner tray (3)



■ Other

User manual

Parts drawing