



## 2 Piece Combo Kit LXT®

# DLX2131TJ

18V

Includes : DHP482 Combi Drill and DTD152 Impact Driver



### Models in kit



**Combi Drill LXT®  
DHP482**



**Impact Driver LXT®  
DTD152**

## Combi Drill LXT®

# DHP482

18V • 62 Nm • 0 – 1 900 min<sup>-1</sup>

**Powerful general-use combi drill with hammer action for professionals**

An efficient drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 62 / 36 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light.



**LXT**

### Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
No load speed	0 - 600 / 1900 min <sup>-1</sup>
Max. fastening torque Hard/Soft	62 / 36 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 9000 / 28500 min <sup>-1</sup>
Max. Drilling Diameter in Wood	38 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Concrete	13 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L <sub>WA</sub> )	93 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	82 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

### User benefits

- 4-pole motor in compact design without torque loss at low power consumption
- Highly efficient and compact machine for professional use
- Optimal handle design
- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site

Link to product - [www.makita.com](http://www.makita.com)



## Impact Driver LXT®

### DTD152

18V • 1/4" • 165 Nm • 0 – 2 900 min<sup>-1</sup>

#### Compact impact driver for quick driving

A compact and light impact wrench with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 165 Nm, suitable for quick driving. A handy LED light for added lighting.



**LXT**

#### ■ Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
No load speed	0 - 2900 min <sup>-1</sup>
Max Fastening Torque Impact Drill	165 Nm
Tightening Capacity Standard Bolt	M5 - M16
Impacts per Minute (IPM)	0 - 3500 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	104 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	93 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Fastening Bolt	10,5 m/s <sup>2</sup>
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Tool weight with battery	1,3 - 1,6 kg
Product Dimensions (L x W x H):	137 x 79 x 238 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion

#### ■ User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low

Link to product - [www.makita.com](http://www.makita.com)



# Related products kit

## Standard AC

821551-8

Makpac case (3)



251314-2

Truss Head Screw M4\*12, Td140D



266622-8

Truss Head Screw M4 X 12



346317-0 (2x)

Belt Hook



784637-8

Screw Bit, Ph2 – S6, 45 Mm, Double



## Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



## Optional AC

821551-8

Makpac case (3)



BL1820B

Battery LXT® 2,0 Ah



BL1830B

Battery LXT® 3,0 Ah



BL1840B

Battery LXT® 4,0 Ah



BL1850B

Battery LXT® 5,0 Ah



BL1860B

Battery LXT® 6,0 Ah



## Other - DHP482

User manual

Parts drawing

## Other - DTD152

User manual

Parts drawing